

Specification Sheet | VP200 HANDHELD ELECTROSTATIC SPRAYER

Compact, unobtrusive and easy to use, the Victory Innovations handheld electrostatic sprayer helps you achieve better coverage in less time. Coat up to 260 square meters on a single tank of fluid, with 70% faster application time compared to traditional trigger sprayers.



SPRAYER SPECIFICATIONS

Sprayer Type	Handheld
Power Module	7 kV
Particle Charge	Positive
Nozzle Sizes	40µm / 80µm / 110µm
Spray Patterns	Cone and 120° fan
Spray Distance	0.61 – 0.91 m
Sound Level	58.5 dBA
Tank Capacity	1 L
Weight (empty)	1.72 kg
Weight (full)	2.68 kg
Flow Rates ¹	40µm nozzle – 91.68 ml/min. 80µm nozzle – 112.38 ml/min. 110µm nozzle – 310.52 ml/min.
Tank Run Time ²	40µm nozzle – 10.9 min. 80µm nozzle – 8.9 min. 110µm nozzle – 3.2 min.
Tanks per Full Battery Charge	40µm nozzle – 22 80µm nozzle – 27 110µm nozzle – 75
Certifications	SAA (JAS-ANZ) RCM cETLus (US & Canada) CE (EU) NOM (Mexico) FCC RoHS WEEE

BATTERY SPECIFICATIONS

Number of Batteries	1
Battery Capacity	3.35 Ah
Voltage	16.8 V
Battery Cycles	800
Battery Technology	Li-ion
Battery Runtime	4 hours
Battery Recharge Time	3 hours
Certifications	SAA (JAS-ANZ) RCM cETLus (US & Canada) CE (EU) RoHS FCC WEEE
IPX Rating	IPX4

¹ Data based on internal testing. ² When constantly spraying.

©2021 Victory Innovations Co. All rights reserved. Victory Innovations and Victory Innovations shield are trademarks or registered trademarks of Victory Innovations Co. and may be registered in certain jurisdictions. All other trademarks belong to their respective owners. Product specifications subject to change without notice. VIC_SS_VP200 Handheld Metric_0321